

SAS ISOLATOR

CRITICAL AIR MONITORING IN ISOLATOR AND BARRIER ENVIRONMENTS

It consists of a programmable unit which remains outside the controlled area and an independent sampling head which uses 55 mm Contact plates (RODAC) or Standard 90 mm Petri dishes

The SAS Isolator features:

- The technical performances are the same as the SAS Super 100 or SAS Super 180
- The sampling head may be positioned anywhere within the isolator
- Minimal disturbance of the unidirectional air flow
- Fast sampling (up to 1000 litres = 1 cubic metre - of air in six minutes)
- Fully programmable from outside
- Compatible with the most commonly used sanitizing and sterilizing agents
- Any type of 55 mm Contact plates (RODAC) or Standard 90 mm Petri dishes may be used



HEAD
15503
23023

PIER
CHAMBER
87085
88826

SAS ISOLATOR
43216 - 43217
43218 - 43219



Connection between
SAS command unit and
aspirating chamber

WHAT TO ORDER

CODE	DESCRIPTION
43216	SAS ISOLATOR air sampler for contact plates with air flow of 100 L/min (without head and battery charger)
43217	SAS ISOLATOR air sampler for contact plates with air flow of 180 L/min (without head and battery charger)
43218	SAS ISOLATOR air sampler for Petri dishes with air flow of 100 L/min (without head and battery charger)
43219	SAS ISOLATOR air sampler for Petri dishes with air flow of 180 L/min (without head and battery charger)
86603	battery charger 220V for SAS ISOLATOR
86604	battery charger 110V for SAS ISOLATOR

Choose your favorite head by consulting the wide range of "ACCESSORIES" page 19